Set Name	Query	Hit Count	Set Name
side by side			result set

DB=USPT; PLUR=YES; OP=ADJ

Set Name	Query	Hit Count	Set Name
L18	(L1 or L9) and L17	1	L18
L17	718/103.ccls.	508	L17
L16	(L1 or L9) and L15	4	L16
L15	719/313-314.ccls.	566	L15
L14	(L1 or L9) and L12	1	L14
L13	(L1 or L9) and L11	1	L13
L12	709/240-241.ccls.	501	L12
L11	709/206-207.ccls.	2042	L11
L10	L9 same message	3	L10
L9	block$ with semaphore with application	28	L9
L8	L1.clm.	1	L8
L7	L1 and wak$	4	L7
L6	L1 same wak$	0	L6
L5	message classes same semaphore	0	L5
L4	message classes same application same semaphore	0	L4
L3	L1 same block$	4	L3
L2	L1 same classes	4	L2
L1	state same application same semaphore same message	47	L1

END OF SEARCH HISTORY

Set Name	Query	Hit Count	Set Name
side by side			result set

DB=PGPB; PLUR=YES; OP=ADJ

Set Name	Query	Hit Count	Set Name
L13	(L1 or L4) and L9	0	L13
L12	(L1 or L4) and L8	4	L12
L11	(L1 or L4) and L7	0	L11
L10	(L1 or L4) and L6	2	L10
L9	718/103.ccls.	108	L9
L8	719/313-314.ccls.	304	L8
L7	709/240-241.ccls.	182	L7
L6	709/206-207.ccls.	3316	L6
L5	L4 same message	2	L5
L4	block$ with semaphore with application	13	L4
L3	L1 same block$	6	L3
L2	L1 same classes	4	L2
L1	application same semaphore same message	97	L1

END OF SEARCH HISTORY